

TECHNICAL DATA

Vapor Shark® Industrial Odor-Neutralizing System

*The Superior **Alternative** to Ozone Generators*

Right Side View



Air inlet

Adjustable vent

Replaceable, nontoxic natural essential oil membranes available. 3X Industrial & S.O.S./ Smoke Odor Solution recommended. (sold separately)



Heavy-duty dual hasps with locking capability

Comfort handle for easy transport

Left Side View



Power switch

Air outlet

6-foot grounded power cord

0.29/0.30-amps,
50/60-hertz,
120-volts,
36-watts,
53 CFM blower

Membrane rack

Durable aluminum case



SUGGESTED APPLICATIONS

- ◆ Fire/Flood Damage Restoration
- ◆ Hydroponic & Grow Rooms
- ◆ Contents Restoration
- ◆ Manufacturing & Industrial Settings

- ◆ Real Estate/Foreclosures
- ◆ Crime Scene/Bioremediation
- ◆ Disaster Recovery
- ◆ Animal & Veterinary Facilities

IMPORTANT

This system provides a safe, effective *alternative* to ozone. It is *not* recommended for use with ozone generating equipment.

Use Xactimate codes: CLN DODRM, CLN DODRME, & CLN DODRMEM

Proudly made in the USA



Pioneering Simple Solutions for Tough Odors Naturally Since 1979

The Vapor Shark®

Powerful Industrial Odor Control

PURPOSE

The Vapor Shark is an easy-to-use, portable system. It treats areas up to 50,000 ft³ (10,000 ft³ per membrane and unit is designed to hold up to five membranes) to effectively eliminate odor contamination quickly and safely. Primarily intended for delivering a fast, high-intensity treatment, it uses Vaportek's patented spill-proof essential oil membranes to release a nontoxic, odor-neutralizing dry vapor into the air. Penetrating vapor quickly controls and eliminates malodor caused by smoke, humidity, food, and biological odors, among others. Based on proven technology originally developed for use in medical facilities, the Vapor Shark sets the standard for treating an area's atmosphere, structure, and contents simultaneously.

PLACEMENT

The Vapor Shark is intended for application where quick results are desired. Place on a firm, stable surface in a relatively high location. Can be used freestanding or permanently installed to air handling systems. For initial treatment, open air inlet a half-inch. After 10-15 minutes, adjust air inlet as necessary to either reduce vapor output (close inlet) or increase vapor output (open farther). When unit is not in use, membrane life may be extended by securely closing the air inlet opening and the front access door. To accelerate the dissipation period of the characteristic Vaportek fragrance, ventilate by opening windows and turning on floor fans. Deodorization may require as little as 15-60 minutes for light contamination. For more severe contamination, treatment may take several hours or days. If necessary, move the unit to different areas. As with any electrical device, do not locate or use near water. For best results, store membranes in a cool, dry location and keep away from extreme heat. Dry vapor output will be affected by humidity, airflow, and temperature. Ideal dry vapor release occurs at 50-80°F. Vapor release significantly increases in excess of 90°F.

DETAILS

Aluminum construction. No evacuation or recovery period is required with Vaportek technology. Not designed for continuous, long-term operation. Membrane life is approximately 270 hours. The system does *not* create moisture or ozone, and will not harm fabric, plants, rubber, adhesives, electrical components, or remove pigment from leather. Vaportek products use natural essential oils. If an allergic reaction occurs, please discontinue use immediately. Wash hands with soap after handling membranes. Do not allow membranes to come in contact with finished surfaces. Dimensions: 14"H x 8"W x 17"L. Weight: 10 lbs. Convenient 2" O.D. couplings allow connection to standard hoses for precise dry vapor delivery. Five year limited warranty. CSA and CUL listed.

✓ **Works Fast**
Odor neutralizer is immediate & permanent.

✓ **Easy-to-Use**
Just remove membrane from barrier bag, unfold, & lay in rack.

✓ **Safe & Environmentally Preferable**
No chemicals or harmful ozone.

✓ **Caution**
Finished surfaces may be damaged by direct contact with oils.

Reorder Information:

Unit Only

Vapor Shark (#90-0950)

Vapor Shark Membranes

Single 3X Industrial (#90-0953)

Single Lemon* (#90-0953-05)

Single S.O.S. (#90-0953-85)

Five-Pack/3X Industrial (#90-0953/5)

Five-Pack/Lemon* (#90-0953-05/5)

Five-Pack/S.O.S. (#90-0953-85/5)

***Note:** Lemon membranes are recommend for use *with* 3X Industrial membranes for odor control with a lighter scent. Because Lemon does not contain the same odor neutralizing capabilities of S.O.S. and 3X Industrial, it is *not* recommend for use by itself.

“Just a quick note to thank you for an effective product . . . Using your Vapor Shark unit for a few days neutralized the unpleasant odor & made a big difference. The ease of use & effectiveness is remarkable.”
—Brayton Management Co., Inc.

“We cannot praise [the Vapor Shark] enough . . . It has saved the day on many of our jobs. We would highly recommend any emergency company to think twice before using any other product.”
—Able Restoration, Inc.



VAPORTEK®

P: 800.237.6367 | F: 262.246.5065

www.vaportek.com

www.facebook.com/vaportek

www.linkedin.com/vaportek

Sussex, WI USA

NOTE: Because we are committed to improving our products, Vaportek reserves the right to change product specifications and/or availability without notice or obligation.