Sentinel Products, Inc.
BETTER SOLUTIONS FOR A CLEANER ENVIRONMENT

Removes urethanes used to install parquet, laminated and wood floors!

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

URETHANE ADHESIVE REMOVER

FORMULA 922

HIGH FLASHPOINT
LOW ODOR FORMULA
RINSES WITH WATER
REMOVES CURED ADHESIVES

PRODUCT DESCRIPTION:

SENTINEL 922 URETHANE ADHESIVE REMOVER is a low-odor, readily biodegradable solution, specifically formulated for cleaning and removing urethane and solvent adhesives used for installing wood floors. 922 rinses with water, leaving no residue behind.



DIRECTIONS:

While 922 works on urethane and solvent-based adhesives, we recommend that you test it on a small area first.

For Removing Urethane and Solvent Adhesives:

1. Wet the entire adhesive surface with 922, using a sprayer or mop. Allow 922 to soak and penetrate for 30-60 minutes, depending on the thickness of the adhesive.
2. Scrape the bulk of the softened adhesive from the surface with a floor scraper (razor scrapers are preferred).
3. If necessary, protect walls, drains, cracks, and other flooring with an absorbent. Reapply 922 and agitate using brooms or stripper pads. Liquefied adhesive can be absorbed using kitty litter, sawdust, etc and then removed.
4. Wash and rinse floor thoroughly with SENTINEL 810 and water to ensure a clean surface. Allow to dry completely.

For Removal of Glued Down Wood Flooring:

1. Cut the wood surface using a circular saw into 6" to 8" squares. Set the saw deep enough to cut through the flooring down to the subfloor but not so deep as to cut the subfloor.
2. Vacuum all sawdust from the floor and from out of cut lines.
3. Apply liberal amounts of 922 to the cut lines using a squeegee or mop making sure that all of the 922 product penetrates the cut lines. Typical coverage should average 75 ft^2/gallon. Allow 922 to soak and penetrate under the wood for 4-8 hours.
4. Using a spade or similar tool, pry up old wood flooring. Squares should be intact and easy to remove with little effort. Once flooring is removed, follow directions for removing adhesives from subfloor.

SPECIFICATIONS:

Coverage for urethane removal will range from 50-125 ft^2/gallon, depending on use.

APPEARANCE	AMBER
APPROXIMATE BOILING POINT	385-437°F
ODOR	SLIGHT
FLASHPOINT	OVER 205°F
pH	NEUTRAL

800-373-0633
www.senpro.com

Sentinel Products, Inc
8901 Wyoming Ave. N.
Brooklyn Park, MN 55445

Sentinel Products, Inc.
BETTER SOLUTIONS FOR A CLEANER ENVIRONMENT