

Drawstring WCPE

| | |
|--------------------------|-------------------------------|
| Product | Polyethylene Laminated Fabric |
| Weight (m ²) | 80 g/m ² |
| Colour | Natural |
| Use | Multi Use |

| Properties | Results |
|-------------------------------|-------------------------------|
| Tape Type | Woven |
| Color | Natural |
| Pick Count (inch) Warp x Weft | 8x8 |
| Coating | UV |
| Color | Transparent/White/Silver LDPE |
| Corona | x |
| Side | Both side Single Coating |
| Coating Weight | 24 g/m ² |
| FR | x |
| Packing Type | Roll |

| PERFORMANCE | | | |
|-------------------------------|------------------|---------------|-------------|
| Property | Test Method | Results | |
| Tensile Grab Strength | ASTM D 751-2008 | Warp: 74 lb | Weft: 65 lb |
| Elongation | | Warp: 24% | Weft: 23% |
| Tear Strength (Trapezoid) | ASTM D 4533-2004 | Warp: 21.3 lb | Weft: 16 lb |
| Bursting Strength (Diaphragm) | ASTM D 751-2008 | 114 psi | |
| Hydrostatic Resistance | ASTM D 751 | Kpa | |

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication. We do not assume any liability whatsoever for the accuracy and completeness of the information. This information is offered as a service and should not be construed as a recommendation and/or engineering advice. We do not assume liability whatsoever in regards to its use. The end user should determine for itself the suitability of the product(s) contained herein for the particular purpose and application to which the product(s) will be applied.

rev. 04/17