

Concrete and Terrazzo Sealer

CONCRETE GUARD

Concrete Guard is formulated to provide the ultimate in concrete protection by using both dual-action technology and hybrid polymers. Concrete Guard is environmentally friendly, VOC- compliant, and provides increased stain suspension and resistance against most contaminants found in kitchens, retail food stores, restaurants, malls, garages, warehouses, distribution centers, etc. While originally formulated to be used in conjunction with hardened concrete floor systems, Concrete Guard may also be used anywhere a clear, high gloss, dual-action concrete protection system is desired.

Concrete Guard is designed for use on previously sealed surfaces, as well as surfaces that have been previously stained or dyed and sealed.



Part Number: 1640-6694 | RTU ph - 7.0 | Contents: One U.S. Gallon (3.79 Litres) | Available in Gallons and 4 x 1 gallon cases

DIRECTIONS

- WARNING KEEP FROM FREEZING -

A small test patch application is always recommended. The test patch must be done using the same applicator, equipment, surface reparation, application technique, and at the same temperatures, relative humidity, airflow conditions, etc., that will exist at the time of the full-scale application.

The surface must be thoroughly clean, dry and free of anything that will prevent Concrete Guard from bonding properly with the concrete.

Polished Concrete: Concrete Guard may be applied over concrete that has been previously treated with a densifier/hardener. Best results are obtained if the surface is burnished two hours after application. Concrete Guard can be diluted 1:1 with water.

Existing Concrete: Concrete Guard should be used full strength on existing concrete (no dilution necessary). Concrete must be a minimum of seven days old before applying

