

Chemsafe® Brands

Product Specifications

Item 57418 (5 gal./pail)



Product Description:

Chemsafe Gold is a water based wetting agent used to apply a hydrotreatment to asbestos fibers prior to removal. It contains powerful surface tension reducing agents, allowing for ultimate moisture penetration and wet out. **Chemsafe Gold** helps to maintain dust free conditions during the removal of asbestos containing materials.

Direction for Use:

Apply the product initially at full strength. Wait a few minutes after the first application and re-spray to insure adequate penetration and saturation of ACM. After determining the proper rate of spray that is effective for the removal project at hand, and documenting acceptable fiber count levels, **Chemsafe Gold** can be diluted with water by not more than 2 parts water to 1 part **Chemsafe Gold**. Air monitoring results will determine the suitability of this procedure.

Product Data:

General ID	Cleaning Compound	Evaporation Rate (butyl acetate = 1)	< 1
Odor	Odorless	Boiling Range	> 212°F
Color	Gold Liquid	Vapor Pressure (mm hg)	N/A
Coverage	The porosity and thickness of the ACM (asbestos containing material) layer will govern the volume of usage per unit of area.	Clean Up	Water
Flash Point	No flash at boil.	Reactivity	Stable
Vapor Density (air = 1)	> 1	Application	Manual or Airless
Solubility in Water	Complete	Shelf Life	1 Year
Specific Gravity (water = 1)	1.020	DOT Shipping Name:	Cleaning Compound, Liquid
Percent Volatile	Not Applicable	Shipping Class	55
		Shipping Weight	5 gal. = 45 lbs. 55 gal. = 497 lbs.
		DOT Hazard Class	Not Regulated