



DrizAir® 1200

This compact, highly maneuverable standard dehumidifier removes moisture from everyday spills and reduces humidity in basements, facilities or on construction sites. A proven and durable favorite for almost 20 years!



FEATURES

- Removes up to 18 gallons a day
- Highly mobile – compact size
- Hot-gas bypass for fast defrost
- Rugged rotomolded housing – stackable!
- Electronic touch-pad controls
- Rigid handle – designed for rugged service
- Semi-pneumatic wheels for easy transport
- Built-in duct attachment ring
- Automatic restart when power is restored after outage
- Stackable: Stack up to two high for storage

SPECIFICATIONS

- **Water removal AHAM (80°F/60%RH):** 64 pts. | 30 L/day
- **Water removal max. (saturation):** 145 pts. | 68.6 L /day
- **Process air output:** 227 CFM
- **Temperature operating range:** 33°F–100°F | 1°C–38°C
- **Air filter:** 4-PRO filter
- **Controls:** Electronic touchpad
- **Dimensions (W × H × D):** 20 × 32 × 19.5 × in. | 50 × 83 × 50 cm
- **Use weight:** 80 lbs. | 36 kg
- **Volts:** 115V
- **Amps:** 6.4A
- **Frequency:** 60Hz
- **Air filter:** 4-PRO filter
- **Drain hose length:** 40 ft. | 12 m
- **Cord length:** 25 ft. | 7.6 m
- **Handle:** Fixed
- **Housing:** Rotomolded polyethylene
- **Wheels:** Semi-pneumatic
- **Safety:** ETL listed to CSA 22.2 #92
- **Xactimate:** WTRDHM

SIZES ▪ OPTIONS

- 104677 (F203-A): One unit