



# Velo Pro Low Profile Airmover

Unbeatable versatility and portability. Precisely control power draw from 1.2–1.9 amps and daisy-chain up to 10 units on a single 15-amp circuit. A built-in kickstand provides a total of five operating positions. Don't need variable speed control? Chose the Velo airmover.

## FEATURES

- Adjust amp draw from 1.2-1.9 amps in .1-amp increments to balance draw in limited power settings
- Variable speed control from 500 (min.) to 885 (max.) CFM.
- Daisy-chain capable with convenient dual outlet.
- Hour meter to track usage and maintenance intervals
- Patented outlet design ensures even, broad-path airflow for fast, consistent drying across all surfaces.
- Five operating positions. Dry floors, ceilings, walls and stairways quickly and efficiently.
- Great portability. Easily carry two units at once - or stack up to six on a hand truck.
- Easiest to maintain. Simply remove fasteners and lift out impeller assembly for cleaning.

## SIZES ▪ OPTIONS

- **F505:** One unit



## SPECIFICATIONS

- **Air movement:** 885 CFM (max.) / 500 CFM (min.)
- **Velocity:** 1930 FPM (max.)
- **Static pressure:** 1.65 in. / H<sub>2</sub>O
- **Weight:** 21 lbs. | 9.52 kg Amps 1.2A–1.9A
- **Volts:** 115V
- **Power:** 185W
- **Frequency:** 60Hz
- **Dimensions (W × H × D):** 18 × 9 × 24 in. | 45.7 × 22.9 × 60.0 cm
- **Cord length:** 15 ft. | 4.6 m
- **Controls:** On/Off switch with variable speed
- **Fan:** 6 blade impeller-type
- **Sound level:** 69 dB
- **Construction:** Rotomolded polyethylene and injection molded ABS housing components; steel wire inlet and outlet grills.
- **Safety:** ETL listed to UL/cUL and CSA standards
- **Xactimate:** WTRDRY