



# Sahara Pro X4 TurboDryer

Produces high velocity airflow for ventilation and to accelerate the evaporation of moisture from structural and other materials. A durable, high performance airmover featuring three speeds and GFCI outlets to connect multiple units. Uses only 2.5 amps at maximum setting.



## FEATURES

- Variable speed control with rotary dial.
- Daisy-chain capability with convenience outlet and circuit breaker.
- Stacks vertically for storage.
- Underside drying vent eliminates wet spots.

## SPECIFICATIONS

- **Airflow:** 867 CFM | 1473 CMH
- **Static pressure:** 0.92 in. (H<sub>2</sub>O) | 229.0 Pa
- **Power/Amps (115V, 60 Hz):** 2.5 A (high speed), 2.2 A (medium), 1.9 A (low)
- **Weight:** 24.3 lbs. | 11.0 kg
- **Dimensions (L x W x H):** 17.4 x 15.0 x 17.3 in. | 44.2 x 38.1 x 43.9 cm
- **Units per 15 amp circuit:** Up to 4 units set to high speed, up to 5 units set to medium speed, or up to 6 units set to low speed.
- **Sound level (avg.):** 63 dB (high speed), 54 dB (medium), 50 dB (low)
- **Control:** Rotary control for variable speed
- **Cord length:** 16 ft. | 4.9 m
- **Construction:** Injection molded polypropylene housing components; injection molded ABS inlet grill; steel wire outlet grill.
- **Safety:** ETL listed to UL/ULc and CSA standards