

» SMART CONTROLS SIMPLIFY DESICCANT DRYING

- Optimized performance
- Temperature and humidity display
- Humidistat to prevent overdrying
- Pints-per-day display

» 33% SMALLER THAN CLOSEST COMPETITOR

» THE MOST VERSATILE DESICCANT ON THE MARKET

- Run on a single 120v circuit for basic operation or use 2 cords to optimize performance
- Highly portable operate on its back for low-clearance areas (GREAT FOR CRAWLSPACES!)
- Includes onboard storage for accessories

» FAMOUS DRI-EAZ DURABILITY

- Sturdy Designed for everyday restoration use and abuse!
- Best warranty in the industry

» GREAT FOR DENSE MATERIALS, HARDWOOD FLOORS AND COOLER ENVIRONMENTS



PROGRAMMABLE HUMIDISTAT







SPCIFICATIONS:

MODEL F533

PROCESS AIR 395 CFM

TESTED REACTIVATION AIR 65 cfm
WATER REMOVAL 118 pints per day

(AT 80°F/60% RH)

(AI 80°F/60% RH) DIMENSIONS (W × H × D) $21.14 \times 33.13 \times 20.25$ in.

(Handle upright = 42. 250 in.)

WEIGHT 95 lbs. | 43.1 kg

CONSTRUCTION Powder-coated steel

POWER 120V / 60 HZ

AMPS (AT 80°F/60%RH) Circuit 1: 11.0; Circuit 2: 10.0

BEST IN INDUSTRY 7 years for the body

LIMITED WARRANTY 2 years on the rotor

1 year parts & labor XACTIMATE CODE WTRDHMD

ACCESSORIES INCLUDED:

- Reactivation Out duct ring
- Reactivation Out heat-resistant ducting, 6", 20 ft. L
- · Air inlet duct ring
- Process air outlet adaptor assembly (optional: F536 – 16" layflat ducting)
- Two power cords, 25 ft. ea.











