

Husqvarna PG 280

Applications

- Perfect for grinding adhesive residue, paint and epoxy on medium-sized concrete areas.
- Efficiently grinds due to high rpm levels and a wide range of discs available for various applications.
- Convenient conversion to edge grinding,

Benefits

- Controlled edge grinding with the edge function and wall protector.
- The self-adjusting floating cover with brush skirt follows the surface and creates a tight seal to prevent dust from entering the surrounding environment.
- The chassis/frame can be separated from the grinding head in less than 30 seconds. The frame folds tightly and can be wheeled around. Having two separate pieces enables the grinder to fit into the trunk of most vehicles.
- The speed is fixed and no settings are required.



CSA Approved

50' 10 gauge extension cord included

	PG 280 220-240 V	PG 280 110-120 V
Item No.	967648706	967648713

Technical Specifications

Power, hp (kW)	3 (2.2)	2 (1.5)
Voltage, V	220 - 240	110 - 120
Plug Type	L6-20	L5-15
Rated current, amps	13	15
UL & CSA approved	Yes	Yes
Power supply	1-Phase	1-Phase
Grinding width, in (mm)	11 (280)	11 (280)
Grinding disc, in (mm)	11 (280)	11 (280)
Grinding disc segment capacity	12	12
Grinding pressure total, lbs (kg)	77 (35)	77 (35)
Grinding disc speed, rpm	1,720	970
Direction of rotation (viewing from operator's position)	Clockwise	Clockwise
Dimensions (L x W x H), in (mm)	47 X 16 X 39 (1,200 X 410 X 1,000)	
Dust port size, in (mm)	2 (51)	2 (51)
Weight, lbs (kg)	154 (70)	154 (70)
Recommended generator size, kW	7.5 - 20A Circuit	6.5 - 20A Circuit
Recommended dust extractor size, CFM	250+	250+



CONVENIENT EDGE GRINDING

A removable section (on left or right) on the lid cover makes it easy to convert to edge grinding. Non-marking wall protector ensures the wall is not damaged.