

Husqvarna PG 540



Applications

- Powerful, compact and versatile planetary floor grinder perfect for smaller jobs.
- Suitable for floor prep, grinding and polishing.
- HIPERFLOOR®
- Wet or dry applications

Benefits

- Sealed grinding head with 1000 hrs service interval. No dust or water can intrude to damage components.
- The optional weights are a must have for every professional grinder, as they allow adjustment of grinding pressure in three pre-set positions. They also make tilting the machine that much easier.
- Dust sealed electrical cabinet with external cooling technology.
- Possibility to log operating hours and read the RPM of the machine.
- Self-adjusting floating cover with brush skirt follows the surface and gives a tight seal to prevent the dust from entering the working environment.
- Fits into most standard cars due to the split-chassis design.



SURFACE PREPARATION

Surface Preparation Model	PG 540
Part No. (1 x 220 V - 30 A)	967977406
Part No. (3 x 200 V - 16 A)	967977404
Part No. (3 x 480 V - 10 A)	967977402

Technical Specifications

Rated input power, hp (kW)	5.5 (4)
Voltage, V	200-480
Rated current, A	10/16/30
Power supply	1-phase/3-phase
Grinding width, in (mm)	20 (500)
Grinding disc, in (mm)	3 x 9 (3 x 230)
Grinding pressure total, lbs (kgs)	165 (75)
Grinding pressure with weights, lbs (kgs)	179-234 (90-115)
Grinding disc speed, rpm	348-1,160
Direction of rotation	Counter Rotation
Transport dimensions, in (mm) (L x W x H)	40 x 22 x 28.9 (1,015 x 560 x 735)
Weights, lbs (kgs)	169/178 (373/392)

Features

Integrated weights	Yes
Connectivity BLEM/Fleet option	No/Yes