

# IBIX | 9 H<sub>2</sub>O

IBIX® 9 features dual action wet and/or dry technology designed for hard to reach work spaces. Perfect for a wide variety of applications, pre-paint preparation and cleaning surfaces, the IBIX® 9 delivers a perfectly consistent air and media flow and notably require only one operator.

- ▶ **Light weight aluminum construction**
- ▶ **Can be run by most small compressors**
- ▶ **Includes Application Gun and Water Nozzle**
- ▶ **Filling Funnel w/Sieve**



**IBIX Systems designed for Multiple Green Abrasives.**  
(Garnet, Calcium, Glass, Walnut and other)



**Adjustable Air Flow**



**VORTEX Technology**



**IBIX 9 Nozzle Kit**

## PRODUCT SPECIFICATIONS

Nozzle	Pressure	58 PSI - (4 bar)	72.5 PSI - (5 bar)	87 PSI - (6 bar)	101.5 PSI - (7 bar)	116 PSI - (8 bar)
Standard 1/8" (3 mm)		13 cfm	14.5 cfm	15.5 cfm	16.7 cfm	17.7 cfm
<b>Also available for this system</b>						
Size 3/32" (2.5 mm)		9 cfm	10 cfm	10.8 cfm	11.5 cfm	12.3 cfm
Size 5/32" (4 mm)		23.2 cfm	25.6 cfm	27.8 cfm	29.8 cfm	31.6 cfm

Item	Description
<b>I9-H2O</b>	IBIX 9 H2O Wet/Dry Surface Prep System
<b>Accessories</b>	
<b>I25-NK</b>	IBIX 9 Nozzle Kit

Pressure adjustable:	3 - 130 PSI (0.2 - 9 bars)
Abrasive range:	20-350 Mesh (2.5 - 0.025 mm)
Hose length:	20 ft. (6 m)
Standard nozzle size:	1/8" (3 mm)
Tank capacity:	2.4 gal. / 0.32 ft <sup>3</sup> / 19.2 lbs (9 liter)

Usage rate:	0.75-1.5 lbs./sq. ft. avg.
Performance:	35-55 sq. ft./h avg.
System height (w/out handle):	25"
System width (w/out front legs):	8" (w/legs 14")
Packaging (box) dimensions:	14x17x31"
Machine net weight (empty tank):	35 lbs. (16 kg)

**Locations Nationwide**  
Visit [www.safetyexpress.com](http://www.safetyexpress.com)  
to find a branch nearest you.