

Safety Products for Hazardous Environments





ZipWall® 20' Spring Loaded Pole Part# KT20

Each ZipWall® KT20 contains two 20 foot Spring Loaded poles (SLPs) and accessories for each pole. The KT20 is ideal for creating dust barriers where ceiling heights are up to 20'. Importantly, you can do this without the use of tape or staples, ladders, hydraulic jacks or scaffolding. Consider this example: A 60 foot long, 19 foot high barrier that takes 9 hours to complete with conventional methods. It also requires an expensive hydraulic jack to raise the barrier sheeting.

With the ZipWall® KT20 system, the same barrier can be completed by two people in about 10 minutes without a hydraulic jack. What's more, no tape means no costly repairs to painted surfaces. The Kit 20 poles extend from 5'2" to 20 feet. Poles should be placed every 8' to 10' or closer if there is a lot of air movement.

All ZipWall poles are ideal for dropped ceilings. Spring Loading automatically adjusts the pole height to compensate for any movement of the grid during setup. Just place the poles so the tops push against the grid, then follow the grid until you've contained the area.

PRODUCT FEATURES

- Pro-quality/durability; provides dust-tight seal at the ceiling without tape or staples
- Height ranges from 5-feet 2-inches to 20-feet
- Accepts sheeting up to 8 mils thick
- Each KT20 contains 2 20-foot poles, 2 spring loaded jacks, 2 tethers, 2 Grip Disks
- Meets strict ANSI certification for quality