



5700[®]

RIDE-ON SCRAPER

5700-AKT, 5700-AUS, 5700-BOL, 5700-EUR, 5700-HER, 5700-JPN, 5700-KAN, 5700-KTU, 5700-UK, 5700-SUN, 5700DL-HER, 5700DL, 5700HS, 5700-LIN



5700 Specifications

Power Supply	Battery	
Width*	24.5"	62 cm
Height	50"	127 cm
Length*	58"	147.32 cm
Weight	2,244 lb	1,017.9 kg
Removable Weight	185 lb front	83.9 kg front
Weight (machine only)	2,059 lb	933.9 kg
Speed	Up to 120 ft/min 160 ft/min for HS	up to 36.6 m/min 48.8 m/min for HS
Voltage	115	230
Frequency	60 Hz	50 Hz

5700DL Specifications

Power Supply	Battery	
Width*	24.5"	62 cm
Height	50"	127 cm
Length*	63"	160 cm
Weight	2,407 lb	1,091 kg
Removable Weight	185 lb front	84 kg front
Weight (machine only)	2,222 lb	1,007 kg
Speed	up to 120 ft/min	up to 36.6 m/min
Voltage	115	230
Frequency	60 Hz	50 Hz

**Measurements are without tooling attached.
Meets the requirements of the Machine Directive 2006/42/EC and EMC Directive 2004/108/EC. It is CE marked.*

5700HS: Designed to cover more space in less time; specifications made to order.
Special Note: the 5700 can be ordered with lifting arms, to make jobsite maneuvering easier.

5700 is available with or without the Dual Lift. The Dual Lift feature adds operator controls for adjusting blade pitch and angle while remaining seated.

SAFETY

- A.** Automatic kill switch is triggered when the operator seat is vacant
- B.** Larger/deepened forklift pockets
- C.** E-stop knob for safety
- D.** Debris deflector protects machine from loose material

COMFORT

- E.** Ergonomic design includes movable foot pegs, taller handles, and an adjustable seat
- F.** Hinged hood system for easy access maintenance

PERFORMANCE

- G.** Precise hydraulic steering for maneuvering in tight spaces, zero turn radius
- H.** Quick-change swivel head blade holder
- I.** Optional dual-lift, hydraulic slide plate adjusts blade pitch and angle for continuous contact with the floor
- J.** Nonmarking tires
- K.** Twelve AGM 180-amp hour batteries provide 100 percent power, speed, and torque for 90 percent of the batteries' run cycle
- L.** Compact design fits through standard door frames and elevator doors
- M.** Front caster wheels allow increased maneuverability in tight spaces
- N.** LED light for increased visibility