



The Omniguard 5

Differential Pressure Monitor

ORDERING INFO

Omniguard 5

Autodialer

Remote Auxiliary Alarm

External Hose Replacement

Thermal Paper (box of 5)

PART NUMBER

IOG4

IOGAUTODIALER

IOGALARM

IOGHOSE10FT

IOGP5

THE WATCHMAN IS IDEAL FOR

Abatement/Remediation Jobs

Restoration Projects

Construction Sites

First Response & Epidemic Control



touch screen

The Omniguard 5 differential pressure recorder is built in a completely self-contained package. This pressure monitor uses real time monitoring of differential pressure and/or vacuum level, with dual inlet ports to allow monitoring between two areas. Multiple reports available at the touch of a key and the view log on screen makes it easy to scroll through the entire memory contents. The USB Type-A port lets you save logs directly to a flash drive as an additional logging option and a second USB port supports PC communication for transferring job logs, real time monitoring and configuration editing.

The Watchman

| | |
|------------------------------------|---|
| Differential Pressure Range | +/- 0.250 inches Water Column (+/- 6.35 mm WC, +/- 62.5 Pascals) |
| Accuracy | +/- 0.003 inches Water Column or +/- 1% of reading whichever is greater |
| Power Requirements | 85-240 VAC 50-60Hz 10W Max (with 6 ft power cord), Internal rechargeable 3.7 Volt Li-ion type battery |
| Controls & Display | 4.3" Color Touchscreen LCD (480 x 272 pixels) |
| Burst Pressure | 3 psi (20 kPa) on either inlet nozzle |
| Alarm | Two programmable alarm settings, 95db audible alarm and red bordered on-screen warning indicate alarm condition |
| Housing | copolymer polypropylene with polycarbonate window in the lid, stainless steel hanging hook |
| Pressure Inlets | (2) 3/16" OD barbed hose connectors, 10 ft of pressure hose provided |
| Size/Weight | 9.25" x 7.5" x 4.5"; 6 lbs. |