OmniPro

Product Sheet

OmniPro™ LGR Dehumidifier

Engineered for Restoration.
Built for Performance.

The OMNIPRO OPD190 is a high-performance **Low Grain Refrigerant (LGR)** dehumidifier, purpose-built for demanding **water damage restoration** applications. With robust moisture removal capabilities and energy-efficient operation, it's your go-to solution for structural drying in residential, commercial, and industrial environments.

Key Features:

- ***Advanced Low Grain Refrigerant system delivers exceptional drying performance even in low humidity environments, accelerating job completion times.***
- ***Removes up to 95 pints/day under AHAM conditions, making it ideal for large-scale restoration jobs.***
- ***Delivers 386 CFM to circulate air efficiently and maximize drying coverage across affected spaces.***
- ***Operates efficiently with a 8.5A draw, enabling multiple units to run on a single circuit — essential for jobs with limited power access.***
- ***Integrated condensate pump with drainage hose for continuous, unattended operation.***
- ***Durable, rotationally molded housing is easy to transport and store, perfect for restoration fleets.***
- ***Intuitive interface for precise humidity control and job tracking.***
- ***Uses R32 refrigerant, offering high efficiency with lower environmental impact.***

Item	Description
Omnipro-OPD190	OmniPro OPD190 LGR Dehumidifier

Dimensions	36" x 21" x 18.5" (H xW xD)
Weight	97lb
Capacity	95Pints/Day@ 80ºF, 60% RH 190 Pints/Day@ 95ºF, 90% RH
Air Movement	386 CFM
Amperage	8.5A

For more Information contact your local Safety Express representative.