

Product Sheet

OmniPro[™] OPD190

Dehumidifier

Engineered with advanced Low Grain Refrigerant (LGR) technology, the OmniPro Dehumidifier is your go-to solution for tackling excess moisture in basements, warehouses, and other high-humidity areas. Its high-performance design delivers exceptional moisture removal, even in cooler temperatures, helping to prevent mold, eliminate musty odors, and safeguard your space and valuables from humidity-related damage.

With eco-conscious R32 refrigerant, the OmniPro combines powerful performance with an environmentally responsible footprint — all without compromising efficiency or effectiveness.

Features:

- ► Hot gas valve system for fast defrost
- ► Easy to assemble disassemble the housing for repair
- ► Fast connect hose for convenient assembly
- ► Easy to operate foldable handle
- ► Tough semi pneumatic wheels
- **▶** Quick pump access in front



Item	Description	
Omnipro-OPD190	OmniPro OPD190 LGR Dehumidifier	

Dimensions	36" x 21" x 18.5" (H xW xD)
Weight	97lb (44kg)
Voltage & Hertz	AC115V / 60Hz
Rated Input Current	6.8A@80ºF, 60% RH
MAX. Input Current	8.5A
Refrigerant Charge	R32/13.06oz

Dehumidify Capacity	95Pints/Day@ 80ºF, 60% RH 190 Pints/Day@ 80ºF, 60% RH
Maximum Design Pressure	High Side: 550psig - Low Side: 260psig
Air Movement	230-240 CFM / 395-405 CMH
Compressor Input	RLA: 6.15A - LRA: 36A
Fan Motor Power	0.75A / 0.11HP

For more Information contact your local Safety Express representative.