

Ultrapac® Renovate (A217)

Powerful hard surface cleaner for heavy-duty fire and restoration cleaning

FOR PROFESSIONAL USE ONLY

Superior performance on heavy soils • Suitable for fire & water damage cleaning

DESCRIPTION

Prochem's Ultrapac Renovate is a powerful, highly concentrated cleaner that removes tough, deeply embedded greasy soils and smoke residues. Use on painted or unpainted surfaces, drywall, metals, some carpets, and other water-cleanable surfaces. Contains no solvents, which can damage some sensitive surfaces. Rinses out easily and leaves no streaks or blotches.

FEATURES

- Highly concentrated, powerful cleaner for fire and smoke restoration
- Removes greasy soils and smoke residues
- Penetrates and removes soils from smooth and porous surfaces
- Rinses freely without streaks and blotches
- · Contains no caustic or solvents

WHERE TO USE

Disaster restoration: Deep cleaning, non-streaking for fast and effective cleaning on fire and smoke damage restoration.

Hard surface cleaning: Excellent cleaner for routine or heavy-duty cleaning on most hard surfaces. Removes tough soils and charged carbon particles left by smoke, soot and air currents.

Walls, flat paint: Wall cleaner for routine or salvage cleaning on walls. Helps eliminate blotchy results often seen on flat paint.

Sealed wood furniture: Reduces need for specialty wood cleaners on sealed, water-cleanable wood.

Pressure washing: Quickly removes oily and carbon particulate soils.

Fire restoration carpet cleaning and filtration soil removal: Removes soot and filtration soil from carpet in salvage situations. See tips below.

USE DIRECTIONS

Pretest: Pretest in an inconspicuous location. Not recommended for use on stain-resistant carpet, most fabrics, unsealed wood, aluminum, or other delicate or water-sensitive surfaces.

Mixing:

Normal soil: Mix 1 ounce per gallon of warm water (1:128).

Heavy soil, restoration cleaning: Mix up to 6 ounces per gallon of warm water (up to 1:21).

Cleaning: Spray or wipe onto surface, scrub if needed, rinse with clear water. Allow 2–5 minutes dwell time before rinsing for additional soil removal.

Pressure washing: Dilute 1:4, meter through pressure washer injection system.

Fire restoration carpet cleaning and filtration soil removal: CAUTION: Removes stain-resist coating from stain-resistant nylon carpets; use ONLY for disaster restoration carpet cleaning. Mix 6 oz. per gallon, pre-spray, and extract. To restore stain-resistance after restorative cleaning, apply Prochem FourGuard Carpet Protector according to label directions.

Tip:

To create a powerful ceiling cleaner, combine Renovate with Prochem's Oxy Plus. Mix 3 oz. Ultrapac Renovate and 1 oz, Oxy Plus per gallon of warm water.

Read label instructions and Safety Data Sheet before using. Product labels and Safety Data Sheets are available at LegendBrandsCleaning.com.

ADDITIONAL REFERENCES available at LegendBrandsCleaning.com

- · Cleaning system guides
- Product User Guides
- · Safety Data Sheets
- · Product labels
- · Tech Tips blog

Boost your skills and knowledge with Legend Brands Education! Taught by leading experts in the cleaning and restoration industry, Legend Brands Education courses enhance your knowledge of cleaning and restoration processes and improve your skills and boost your profitability. Courses are hosted at distributor locations throughout North America and held in hands-on training facilities located in Burlington, Wash., and Nashville, Tenn. For more information, visit LegendBrandsEducation.com or call 800-932-3030.

Ultrapac Renovate Technical Data	
Color	Yellow
Odor	Citrus
Appearance	Opaque liquid
VOCs	See Safety Data Sheet
pH of ready-to-use:	10.0 to 11.0