



Revolution LGR

Compact, stackable and easy to transport, the Revolution's space-saving design and state of the art technology lets you bring high performance drying power to every task. Features the new [Command Hub](#), compatible with the new [Command Center App](#). Take advantage of [Bluetooth](#) and [WiFi](#) connectivity to control the dehu and view jobsite conditions remotely. Available now in the [Apple Store](#) and [Google Play Store](#).



FEATURES

- **Command Center App Users!** For dehu firmware update instructions, visit [Mastering your Dri-Eaz Command Center](#) and scroll down to "Update Your Dri-Eaz Dehumidifier's Command Hub Firmware."
- **Quick Tip:** To connect to the Command Center App to WiFi and enable remote control and monitoring, visit our [FAQ page](#) scroll down to "How to connect Command Center mobile app to WiFi."
- NEW! Command Hub touchscreen controller displays real-time temp, RH, grain depression and drying progress trends at a glance. Controller integration product for existing i-Series dehumidifiers also available. [Learn more](#).
- Small, light Xactimate "Large" category dehu – more water removal than units 2–3 times its size!
- Delivers "Large" dehu performance yet fits where others don't – crawlspaces, bathrooms, kitchens, etc.
- Fast and convenient access to humidistat, job hours, maintenance reminders and more.
- Secure, compact stacking – transport multiple units on a handtruck.
- Fastest access inside unit for cleaning.
- Fit more drying in the truck, make fewer trips – make more profit!

SPECIFICATIONS

- **Water removal:** 80 pts./day | 38 L/day at 80°F/60%RH (AHAM)
139 pts./day | 66 L/day at 90°F/90%RH
- **Air movement:** 121–180 CFM | 206–306 CMH
- **Dimensions (W × H × D):** 12.5 × 17.6 × 21.5 in. | 31.8 × 44.7 × 54.6 cm
- **Housing:** Rotomolded polyethylene
- **Weight (w/cord & hose):** 65 lbs. | 29.5 kg
- **Amps:** 6.2A (at 80°F/60%RH)
- **Volts:** 115V
- **Frequency:** 60Hz
- **Sound level (avg.):** 55 dB
- **Operating range:** 33°F–100°F | 1°C–38°C
- **Air filter:** 4-PRO filter
- **Safety:** ETL listed to CSA standards
- **Xactimate:** WTRDHM>L

SIZES ▪ OPTIONS

- 111995 (F413): One unit