

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

SURFACTANT WETTING AGENT

FORMULA

840

WATER-BASED
SUPERIOR WETTING AGENT
HIGH PENETRATION RATES
READY-TO-USE

PRODUCT DESCRIPTION:

Sentinel 840 Surfactant Wetting Agent is a superior wetting agent designed for use prior to the abatement of asbestos containing materials (ACM). Sentinel 840 saturates fibers and lowers surface tension which aids in reducing the release of fibers and dust during removal.

DIRECTIONS: (Always follow product label instructions for best results.)

Apply Sentinel 840 at full strength directly to material to ensure adequate penetration and saturation. Reapply if necessary or as indicated by fiber count levels. Air monitoring results will determine when reapplication is necessary. Sentinel 840 can be applied with most spray equipment at low pressure settings.



- Product should not be diluted.
- Do not apply product to materials with a temperature of more than 212° F or below 32°F.
- Always adhere to all regulations mandated by OSHA and EPA Guidelines when using this product for the removal of asbestos containing materials.
- This product does not contain asbestos.

For additional information or assistance with this product, please call Sentinel Customer Service at, 800-373-0633.

SPECIFICATIONS:

SURFACE TENSION:	< 27 dynes/cm
APPEARANCE	CLEAR
APPROXIMATE BOILING POINT	>212°F
ODOR	NO ODOR
SPECIFIC GRAVITY(H ₂ O=1)	~1.0
FLASHPOINT	None to Boiling