









LGR DEHUMIDIFIER

CRUSHES IT FOR PORTABILITY & PERFORMANCE

125 PINTS/DAY AT AHAM AND MORE THAN 40% HIGHER WATER REMOVAL AT LOW GRAINS

UNRIVALED WATER REMOVAL **ACROSS ALL DRYING CONDITIONS**

- EXTREME DEW POINT TECHNOLOGY™ Sensor-driven, optimized response to changing conditions – for ultimate drying
- TIME-SAVING I-SERIES CONTROL displays GPP, inlet and outlet temp and RH, plus maintenance prompts
- TRULY FAST 4-BOLT ACCESS for cleaning and preventative maintenance
- AMAZINGIY OUIFT AND POWERFUL!

THE ONE DEHU CUSTOMERS WILL CHOOSE FIRST FOR EVERY JOB!



POWER

WATER REMOVAL AHAM (80°F/60%RH)

WATER REMOVAL MAX (MAX. AT SATURATION)

PROCESS AIR (MAX.)

FILTER TYPE

(HxDxW) **USE WEIGHT**

CONSTRUCTION DURABLE ROTOMOLDED

MODEL SYCLONE XL LGR 8 AMPS, 115V

125 PINTS | 59 LITERS / DAY

210 PINTS | 99.4 LITERS / DAY

320 CFM | 544 CMH. FLOOR-LEVEL OUTLET 4-PRO FILTER 24 PACK F579 (SAME AS DRIZAIR 1200)

DIMENSIONS 32.1 × 19.8 × 20.0 IN 81.5 × 50.3 × 50.8 CM 106 LBS. | 48 KG DRAIN HOSE 40 FT. | 12.2 M POWER CORD 25 FT. | 7.6 M

POLYETHYLENE SHELL



800.465.3898

safetyexpress.com

fibreclean.com

OUTLET

selectoro.ca