

Product Sheet



LGR DEHUMIDIFIER

CRUSHES IT FOR PORTABILITY & PERFORMANCE

125 PINTS/DAY AT AHAM AND MORE THAN **40% HIGHER WATER REMOVAL AT LOW GRAINS**

UNRIVALED WATER REMOVAL ACROSS ALL DRYING CONDITIONS

- EXTREME DEW POINT TECHNOLOGY™ Sensor-driven, optimized response to changing conditions – for ultimate drying
- TIME-SAVING I-SERIES CONTROL displays GPP, inlet and outlet temp and RH, plus maintenance prompts
- TRULY FAST 4-BOLT ACCESS for cleaning and preventative maintenance
- AMAZINGLY QUIET AND POWERFUL!

THE ONE DEHU **CUSTOMERS WILL CHOOSE** FIRST FOR EVERY JOB!



WATER REMOVAL AHAM (80°F/60%RH) WATER REMOVAL MAX (MAX. AT SATURATION)

PROCESS AIR (MAX.)

FILTER TYPE

(HxDxW)

POWER CORD 25 FT. | 7.6 M CONSTRUCTION

MODEL SYCLONE XL LGR POWER 8 AMPS, 115V

125 PINTS | 59 LITERS / DAY

210 PINTS | 99.4 LITERS / DAY

320 CFM | 544 CMH. FLOOR-LEVEL OUTLET

4-PRO FILTER 24 PACK F579 (SAME AS DRIZAIR 1200) **DIMENSIONS** 32.1 × 19.8 × 20.0 IN

81.5 × 50.3 × 50.8 CM USE WEIGHT 106 LBS. | 48 KG DRAIN HOSE 40 FT. | 12.2 M

> DURABLE ROTOMOLDED POLYETHYLENE SHELL.



For more Information contact your local Safety Express representative.