

# Conversion guide for 3M™ Secure Click™ Half Facepiece Reusable Respirator HF-800 Series.



Designed with smart and intuitive features, the 3M™ Secure Click™ Half Facepiece Reusable Respirator helps protect workers from particulates and a wide variety of gases and vapours when used with approved 3M™ Secure Click™ Filters and Cartridges shown below.

*Note: initial offering shown (watch for more to follow).*

If you are currently using a 3M respirator with a bayonet connection, this guide offers conversion suggestions to help you transition to 3M™ Secure Click™ Reusable Respirator.

	Gas and Vapour Cartridges	Combination Cartridges
<b>Bayonet Connection</b>	 6001 OV  6003 OV/AG  6006 MG/V	 60921 OV/P100  60923 OV/AG/P100  60926 MG/V/P100
<b>3M™ Secure Click™ Connection</b>	 D8001 OV  D8003 OV/AG  D8006 MG/V	 D80921 OV/P100  D80923 OV/AG/P100  D80926 MG/V/P100
	P95 Particulate Filters	P100 Particulate Filters
<b>Bayonet Connection</b>	 2071  2076HF*  2078**	 2091  2096*  2097***
<b>3M™ Secure Click™ Connection</b>	 D3071  D3076HF*  D3078**	 D3091  D3096*  D3097***
	Replaceable Particulate Filters	Replaceable Filter Retainer
<b>Bayonet Connection</b>	 5N11 N95  5P71 P95	 501 Filter Retainer
<b>3M™ Secure Click™ Connection</b>	 D7N11 N95  D7P71 P95	 D701 Filter Retainer

\* 3M recommended for relief against nuisance levels of acid gases. Nuisance level acid gas refers to concentrations less than the OSHA PEL or applicable government occupational exposure limits, whichever is lower.

\*\* 3M recommended for relief against nuisance levels of organic vapour/acid gases. Nuisance level organic vapour/acid gas refers to concentrations less than the OSHA PEL or applicable government occupational exposure limits, whichever is lower.

\*\*\* 3M recommended for relief against nuisance levels of organic vapours. Nuisance level organic vapour refers to concentrations less than the OSHA PEL or applicable government occupational exposure limits, whichever is lower.



## WARNING

These respirators help protect against certain airborne contaminants. Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging. A written respiratory protection program must be implemented meeting all the requirements of OSHA 1910.134 including training, fit testing and medical evaluation. In Canada, CSA standards Z94.4 requirements must be met and/or requirements of the applicable jurisdiction, as appropriate. Misuse may result in sickness or death. For correct use, see supervisor and User Instructions, or call 3M PSD Technical Service in Canada at 1-800-267-4414 and in USA at 1-800-243-4630.