

Chemsafe[™] **SOLVEX 500**

HIGH VISCOSITY-CLEAR POST-REMOVAL LOCKDOWN ENCAPSULANT

Chemsafe [™] Solvex 500 Clear is a premixed post removal lockdown encapsulant used for the lockdown of microscopic asbestos fibers. Chemsafe®500 clear lockdown is essential for use during the mandatory sealing of residual asbestos fibers subsequent to asbestos removal.



Directions For Use:

For best results, mix this product thoroughly (5-10 minutes) before and during use. Apply with an airless sprayer. Dispose of in accordance with federal, state and local regulations.

Clean-Up: Clean spray equipment and tools immediately after use with warm water prior to product drying.

ltem	Description
2664-0779	Chemsafe™ Solvex 500 Clear 5 Gallon Pail (ea)
2666-0771	Chemsafe™ Solvex 500 Clear 275 Gallon Tote (ea)

General ID	Lockdown
Odor	Negligible
Color	White-dries clear
Flash Point	N/A
Vapor Density	1
Solubility in Water	100%
Specific Gravity (water=1)	1.01

PRODUCT DATA

Boiling Range	212° F.
Coverage	300-500 Sq Ft per gl
Clean Up	Soap & Water
Reactivity	Stable
Application	Brush/Roller/Airless
Shelf Life	2 Years Unopened
V.O.C. Content	11.36 g/L
Shipping Weight	5 gal. = 45 lbs 55 gal. = 495 lbs
DOT Shipping Name	Not Regulated
DOT Hazard Class	Not Regulated

800-465-3989 safetyexpress.com

TORONTO | VANCOUVER | KELOWNA | CALGARY | EDMONTON | SASKATOON | WINNIPEG | OTTAWA | MONTRÉAL | QUÉBEC | MONCTON | HALIFAX