

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

## LOW MASTIC ODOR MASTIC REMODER STATEMENT OF THE PROPERTY OF TH

## PI 145

ECONOMICAL FORMULA LOW ODOR FORMULA HIGH COVERAGE RATES REMOVES BLACK MASTIC

## PRODUCT DESCRIPTION:

Sentinel PL145 Low Odor Mastic Remover is an economically-priced mastic remover made specifically for the removal of black mastic found during the abatement of asbestos containing VAT and VCT tile. PL145 does not contain asbestos.

## **DIRECTIONS:** (Always follow product label instructions for best results.)

Step One: Before beginning work, be sure to protect all walls, flooring, carpeting cracks, or wood with an absorbent (rags, kitty litter, sawdust) to keep liquified mastic contained. This will ensure easier cleanup and reduce potential problems with the installation of new flooring.

Step Two: Once the floor tile is removed, apply PL145 to the mastic using a sprayer or mop to evenly distribute the material. Allow product to soak and penetrate for 10-15 minutes.

Step Three: Using scrapers, remove the softened adhesive from the floor. Reapply product to remaining residue. Repeat as necessary.

Step Four: Using brooms or floor scrubbers, agitate remaining mixture and remove all liquids using absorbents. Step Five: Once the mastic and remover are removed, wash all remaining residue from the floor with a soap and water mixture. Allow the floor to dry completely before installing new flooring.

For additional information or assistance with this product, please call Sentinel Customer Service at, 800-373-0633.

SPECIFICATIONS:

APPEARANCE CLEAR
APPROXIMATE BOILING POINT 400-450°F
ODOR LOW

FLASHPOINT 145°F(Minimum)

Coverage rates for PL145 will range from 80-150 square feet per gallon for mastic removal.



1.800.465.3898

safetyexpress.com