

Bulk Bags | UN-Rated

An effective means of disposal for hazardous and non-hazardous waste. UN-rated for the safe handling and transportation of dangerous goods. Ideal for bulk waste removal, contaminated soil removal or, asbestos containment and removal.

- ▶ **UN-Rated for packaging dangerous goods**
- ▶ **Heavy-duty corner straps - Forkliftable**
- ▶ **Woven polypropylene resists UV and water**
- ▶ **Collapsible for easy storage.**



Item	Description
T222-6	X-Guard UN-Rated Bulk Bag 2200 LB Capacity 38" x 38" x 42" w/ 6mil Liner

TECHNICAL DATA SHEET : PP WOVEN SUPER SACK (UN) DIMENSIONS SIZE : 95X95X105 CMS (38"x38"x42")

REFERENCE :	T 222-6
CAPACITY 1000 kg	
FIBC Bags	CIRCULAR
external dimensions	95x95x115 cm
internal dimensions	95x95x105 cm(38"x38"x42")
PP density	150 gr/m ²
lamination	None
leak proof seams	None
capacity	1000 kg
safety coefficient	6/1
anti-UV treatment	150 kly
Straps	4
Type of FIBC	UN Rated
Usefull length	25 cm
Colour	White
PE Liner	Transparent (150 Microns - 6 Mil)
Skirt filling	YES + 2 fastenings
Dimensions (H)	70 cm
Construction	70 gr/m ²
Lamination	NO
Option	
Document case	None
Safety label	
Printing	1 colours - 2 faces - ASBESTOS printing conforming to UN Norms/Customer Requirements
Packing	200 Pieces / Pallet - 48 Palets/Container (40')
Manufacturing Norms	UN 13 H 3 Y for 1000 Kgs.

[For more information contact your local Safety Express](#)